

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B24B 37/04, 53/007	A1	(11) International Publication Number: WO 99/50024 (43) International Publication Date: 7 October 1999 (07.10.99)
(21) International Application Number: PCT/JP99/01543 (22) International Filing Date: 26 March 1999 (26.03.99) (30) Priority Data: 10/96971 26 March 1998 (26.03.98) JP (71) Applicants (for all designated States except US): EBARA CORPORATION [JP/JP]; 11-1, Haneda Asahi-cho, Ohta-ku, Tokyo 144-8510 (JP). KABUSHIKI KAISHA TOSHIBA [JP/JP]; 72, Horikawa-cho, Saiwai-ku, Kawasaki-shi, Kanagawa 210-8520 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): KIMURA, Norio [JP/JP]; #408, 5-11, Kugenumashinmei 1-chome, Fujisawa-shi, Kanagawa 251-0021 (JP). ISHII, You [JP/JP]; 3204-442, 2-3, Shiomidai 3-chome, Isogo-ku, Yokohama-shi, Kanagawa 235-0022 (JP). TATEYAMA, Yoshikuni [JP/JP]; #505, 25-16, Mitsuke-cho, Hiratsuka-shi, Kanagawa 254-0045 (JP). (74) Agents: WATANABE, Isamu et al.; Gowa Nishi-Shinjuku Building 4F, 5-8, Nishi-Shinjuku 7-chome, Shinjuku-ku, Tokyo 160-0023 (JP).		(81) Designated States: KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: POLISHING APPARATUS

(57) Abstract

A polishing apparatus has a turntable (20) with a polishing cloth (5) attached thereto and a top ring (3) for holding and pressing a workpiece (2) to be polished against the polishing cloth (5) under a certain pressure. The polishing apparatus also has a first dressing unit (11) having a contact-type dresser (10) for dressing the polishing cloth (5) by bringing the contact-type dresser (10) in contact with the polishing cloth (5), and a second dressing unit (16) having a noncontact-type dresser (15) for dressing the polishing cloth (5) with a fluid jet applied therefrom to the polishing cloth (5). The contact-type dresser (10) comprises a diamond dresser or an SiC dresser.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LR	Sri Lanka	SE	Sweden		
DK	Denmark		Liberia	SG	Singapore		
EE	Estonia						

DESCRIPTION
POLISHING APPARATUS

Technical Field

5 The present invention relates to a polishing apparatus
for polishing a workpiece such as a semiconductor wafer to a
planar finish, especially a device pattern on the surface of
the semiconductor wafer by bring the surface of the semiconductor
wafer in contact with a polishing cloth, and particularly to
10 a method of conditioning the surface of a polishing cloth
attached to a turntable in the polishing apparatus.

Background Art

Recent rapid progress in semiconductor device integration
15 demands smaller and smaller wiring patterns or interconnections
and also narrower spaces between interconnections which connect
active areas. One of the processes available for forming such
interconnection is photolithography. Though the
photolithographic process can form interconnections that are at
20 most 0.5 μm wide, it requires that surfaces on which pattern images
are to be focused by a stepper be as flat as possible because the
depth of focus of the optical system is relatively small.

It is therefore necessary to make the surfaces of
semiconductor wafers flat for photolithography. One customary
25 way of flattening the surfaces of semiconductor wafers is to polish
them with a polishing apparatus, and such a process is called
Chemical Mechanical Polishing (CMP) in which the semiconductor
wafers are chemically and mechanically polished while supplying
an abrasive liquid comprising abrasive grains and chemical
30 solution such as alkaline solution.

In the polishing apparatus for polishing the surface of
a semiconductor wafer, especially a device pattern on the upper

surface of a semiconductor wafer, to a planar finish, as a polishing cloth attached to a turntable, a nonwoven fabric polishing cloth has heretofore been employed.

Higher levels of integration achieved in recent years for
5 ICs and LSI circuits demand smaller steps or surface irregularities on the polished surface of the semiconductor wafer. In order to meet such a demand, it has been proposed to employ a polishing cloth made of a hard material such as polyurethane foam.

10 After the semiconductor wafers are contacted with the polishing cloth and polished by rotating the turntable and the top ring which holds the semiconductor wafer, the polishing capability of the polishing cloth is gradually deteriorated due to a deposit of abrasive grains and ground-off particles of the
15 semiconductor material, and due to changes in the characteristics of the polishing cloth. Therefore, if the same polishing cloth is used to repeatedly polish semiconductor wafers, the polishing rate of the polishing apparatus is lowered, and the polished semiconductor wafers tend to suffer polishing
20 irregularities. Therefore, it has been customary to condition the polishing cloth according to a process called "dressing" for recovering the surface of the polishing cloth before, or after, or during polishing.

There are basically two types of dressing processes, one
25 of which is a contact-type dressing process in which a brush or a diamond dresser is brought into contact with a polishing cloth and rubs the polishing cloth, and the other of which is a noncontact-type dressing process in which a fluid jet of water or gas is applied under high pressure to the surface of the
30 polishing cloth.

In the conventional polishing apparatus, either a dressing unit comprising a brush or a diamond dresser or a dressing unit

employing a fluid jet has been incorporated therein, depending on the properties of a polishing cloth.

It has been found that when a new polishing cloth starts to be used, it needs to be dressed by a brush or a diamond dresser
5 for initial conditioning, and while the polishing cloth is being used in a polishing process, it needs to be dressed by a fluid jet to remove an aggregate of abrasive slurry or ground -off particles of the semiconductor material therefrom. Unless the polishing cloth is dressed by the fluid jet, the polished surface
10 of the semiconductor wafer is liable to be scratched, resulting in a poor yield of properly polished semiconductor wafers. For the above reasons, these two dressing units are required to be replaced with each other, when necessary, in the conventional polishing apparatus. Such a selective installing and replacing
15 work has been tedious and time-consuming, and is liable to lower the throughput of the semiconductor wafers.

Disclosure of Invention

It is therefore an object of the present invention to
20 provide a polishing apparatus which incorporates both a contact-type dressing unit having a brush or a diamond dresser and a noncontact-type dressing unit employing a fluid jet.

Another object of the present invention is to provide a method of conditioning the surface of a polishing cloth attached
25 to a turntable in such a polishing apparatus.

According to one aspect of the present invention, there is provided a polishing apparatus comprising: a turntable with a polishing cloth attached thereto; a top ring for holding and pressing a workpiece to be polished against the polishing cloth
30 under a certain pressure; a first dressing unit having a contact-type dresser for dressing the polishing cloth by bringing the contact-type dresser in contact with the polishing

cloth; and a second dressing unit having a noncontact-type dresser for dressing the polishing cloth with a fluid jet applied thereto.

According to another aspect of the present invention,
5 there is provided a method of conditioning a polishing cloth attached to a turntable for polishing a workpiece, comprising: dressing the polishing cloth with a first dressing unit having a contact-type dresser as initial conditioning when the polishing cloth starts to be used; and dressing the polishing
10 cloth with a second dressing unit having a noncontact-type dresser between polishing processes, each for polishing the workpiece.

According to still another aspect of the present invention, there is provided a method of conditioning a polishing cloth
15 attached to a turntable for polishing a workpiece, comprising: dressing the polishing cloth with a first dressing unit having a contact-type dresser as initial conditioning when the polishing cloth starts to be used; and dressing the polishing cloth first with the first dressing unit and then with a second
20 dressing unit having a noncontact-type dresser between polishing processes, each for polishing the workpiece.

The polishing apparatus is equipped with both the contact-type dressing unit such as a diamond dresser and the noncontact-type dressing unit such as a fluid jet dresser.
25 Therefore, it is not necessary to replace these contact-type and noncontact-type dressing units with each other on the polishing apparatus, but the contact-type and noncontact-type dressing units may be combined to carry out a desired pattern of dressing processes to dress or condition the polishing cloth.

30 The above and other objects, features, and advantages of the present invention will become apparent from the following description when taken in conjunction with the accompanying

drawings which illustrate a preferred embodiment of the present invention by way of example.

Brief Description of Drawings

5 FIG. 1 is a plan view of a polishing apparatus according to the present invention;

 FIG. 2 is an elevational view, partly in cross section, taken along line II - II of FIG. 1;

 FIG. 3A is a bottom view of a diamond dresser in a first
10 dressing unit incorporated in the polishing apparatus;

 FIG. 3B is a cross-sectional view taken along line a - a of FIG. 3A;

 FIG. 3C is an enlarged view of an encircled area b in FIG. 3B;

15 FIG. 4 is an elevational view of a second dressing unit comprising a fluid jet dresser incorporated in the polishing apparatus; and

 FIGS. 5A and 5B are timing charts of different patterns of polishing and dressing sequences carried out by the polishing
20 apparatus.

Best Mode for Carrying Out the Invention

Next, a polishing apparatus according to the present invention will be described with reference to drawings.

25 As shown in FIGS. 1 and 2, a polishing apparatus according to the present invention comprises a turntable 20 and a top ring unit 4 having a top ring 3 for holding a semiconductor wafer 2 to be polished and pressing the semiconductor wafer 2 against the turntable 20. The turntable 20 is coupled to a motor 21 by
30 a vertical shaft, and rotatable about the vertical shaft. A polishing cloth 5, such as IC-1000 manufactured by Rodel, Inc., is attached to the upper surface of the turntable 20.

A pusher 40 is positioned on one side of the turntable 20 adjacent to the top ring unit 4. The top ring unit 4 is angularly movable in a horizontal plane to move the top ring 3 between a transfer position above the pusher 40 where the semiconductor wafer 2 is transferred to and from the pusher 40, a polishing position over the turntable 20, and a standby position off the turntable 20. The top ring 3 is coupled to a motor and a lifting/lowering cylinder (not shown). The top ring 3 is vertically movable by the lifting/lowering cylinder and is also rotatable about its own axis by the motor as indicated by the arrows (see FIG. 2). When the top ring 3 is lowered toward the turntable 20, the top ring 3 presses the semiconductor wafer 2 against the polishing cloth 5 on the turntable 20 under a predetermined pressure. The top ring 3 has a holding mechanism (not shown) for holding the semiconductor wafer 2 by its lower surface under a vacuum. A guide ring 6 is mounted on a lower outer circumferential surface of the top ring 3, whereby the semiconductor wafer 2 is retained against removal from the lower surface of the top ring 3. An abrasive liquid containing abrasive grains is supplied to the polishing cloth 5 on the turntable 20 by an abrasive liquid supply nozzle (not shown) which is positioned above the turntable 20.

The polishing apparatus also has a first dressing unit 11 having a contact-type dresser 10, and a second dressing unit 16 having a noncontact-type dresser comprising a plurality of water jet nozzles 15. The first dressing unit 11, which is positioned diametrically opposite to the top ring unit 4 and the pusher 40 across the turntable 20, is angularly movable in a horizontal plane between a dressing position over the turntable 20 and a standby position off the turntable 20. As shown in FIG. 2, the dresser 10 is connected to a motor 17 and a lifting/lowering cylinder 18. The dresser 10 is vertically movable by the

lifting/lowering cylinder 18 and is also rotatable about its own axis by the motor 17 as indicated by the arrows (see FIG. 2).

FIGS. 3A, 3B, and 3C show in detail the dresser 10 of the first dressing unit 11. As shown in FIGS. 3A, 3B and 3C, the dresser 10 comprises a circular disk-shaped dresser body 12 having an annular projection 12a extending along a lower circumferential edge thereof and having a predetermined radial width. The dresser 10 will also be referred to as a diamond dresser 10. The dresser 10 has an electrodeposited diamond ring 13 which comprises fine grains of diamond electrodeposited on the lower surface of the annular projection 12a. Specifically, the electrodeposited diamond ring 13 is produced by attaching fine grains of diamond to the lower surface of the annular projection 12a and then plating the lower surface of the annular projection 12a with nickel for thereby fixing the fine grains of diamond with a plated nickel layer.

In operation, while the turntable 20 and the dresser 10 are rotated relatively to each other, and a dressing liquid such as pure water or an abrasive liquid is supplied from a nozzle (not shown) to a substantially central region of the polishing cloth 5, the lower surface of the electrodeposited diamond ring 13 is held against the upper surface of the polishing cloth 5 to scrape off a thin layer of the polishing cloth 5 for thereby dressing the polishing cloth 5.

The dresser body 12 has a diameter of 250 mm, and the electrodeposited diamond ring 13 on the lower end of the annular projection 12a has a radial width of 6 mm. As shown in FIG. 3A, the electrodeposited diamond ring 13 comprises a plurality of equal arcuate sectors (eight in the illustrated embodiment). The diameter of the dresser body 12 is greater than the diameter of the semiconductor wafer 2 to be polished. When the

semiconductor wafer 2 is polished, therefore, the dressed surface of the polishing cloth 5 provides an extra margin with respect to the polished surface of the semiconductor wafer 2 in both radially inward and outward directions of the turntable 20. The dresser 10 may be replaced with an SiC dresser having a ring of sectors made of silicon carbide. The SiC dresser has a structure identical to the structure shown in FIGS. 3A - 3C, and has on the surfaces of its sectors a number of pyramidal projections each having a height of about several tens of μm .

FIG. 4 shows structural details of the second dressing unit 16. As shown in FIG. 4, the second dressing unit 16 comprises an array of six water jet nozzles 15 positioned over the polishing cloth 5 and equally spaced radially of the polishing cloth 5. The water jet nozzles 15 are fixedly mounted on a water jet nozzle arm 22 having a liquid passage 22a defined therein. Pure water supplied from a pure water source (not shown) is pressurized by a pump 26 and supplied through a tube 23 and the liquid passage 22a to the water jet nozzles 15, from which pure water jets are ejected downwardly toward the polishing cloth 5.

The water jet nozzles 15 are positioned and oriented to apply the pure water jets ejected therefrom to an area of the polishing cloth 5 which is used to polish the semiconductor wafer 2, i.e., an area of the polishing cloth 5 against which the semiconductor wafer 2 is pressed so as to be polished. The water jet nozzle arm 22 is fixed in a position above the polishing cloth 5 by a vertical support 22b. However, the water jet nozzle arm 22 may be angularly movable in a horizontal plane about the vertical axis of the vertical support 22b for fine positional adjustment thereof and/or for standby position located radially outwardly of the polishing cloth 5 for maintenance thereof.

The pure water flowing through the water jet nozzle arm

22 is kept at a predetermined pressure by a controller (not shown) for the pump 26. The water jet nozzles 15 are identical in structure to each other, so that they eject respective water jets under substantially the same pressure at substantially the same rate. The pressure of the ejected water jets can be maintained in the range of 5 to 30 kg/cm² by controlling the pump 26.

When the polishing cloth 5 is dressed by the second dressing unit 16, the turntable 20 and hence the polishing cloth 5 are rotated to thereby apply the water jets ejected from the water jet nozzles 15 to the entire surface of the polishing cloth 5. Since the polishing cloth 5 is held in contact with the water jets for a period of time which is progressively shorter in the radially outward direction, the dressing effect on the polishing cloth 5 which is caused by the water jets may vary depending on the radial position on the polishing cloth 5. Therefore, in order to uniformize the dressing effect on the polishing cloth 5, the number of water jet nozzles 15 may be increased in the radially outward direction, or the water jet nozzles 15 may eject water jets at a progressively higher speed in the radially outward direction. Alternatively, the distance between the nozzle outlet and the polishing cloth 5 may vary from nozzle to nozzle. Further, the pressure and the speed at which the water jet is ejected may be made variable at each of the water jet nozzles 15.

Polishing and dressing processes which are carried out by the polishing apparatus shown in FIGS. 1 through 4 will be described with reference to FIGS. 5A and 5B. FIGS. 5A and 5B are timing charts of different patterns of polishing and dressing sequences carried out by the polishing apparatus.

According to the pattern of polishing and dressing sequences shown in FIG. 5A, when the polishing cloth 5 starts

to be used, it is first dressed by the diamond dresser 10 for initial conditioning. Thereafter, a semiconductor wafer 2 is polished using the dressed polishing cloth 5. Between polishing processes, the polishing cloth 5 is dressed by the water jet nozzles 15 with water jets ejected therefrom.

According to the pattern of polishing and dressing sequences shown in FIG. 5B, when the polishing cloth 5 starts to be used, it is first dressed by the diamond dresser 10 for initial conditioning. Thereafter, a semiconductor wafer 2 is polished using the dressed polishing cloth 5. Between polishing processes, the polishing cloth 5 is dressed in two steps, i.e., first by the diamond dresser 10 and then by the water jet nozzles 15 with water jets ejected therefrom.

As shown in FIGS. 5A and 5B, according to the polishing apparatus of the present invention, after initial conditioning of the polishing cloth 5 by the diamond dresser 10, polishing process of the semiconductor wafer is carried out, and after completing the polishing process, dressing of the polishing cloth 5 by the wafer jet is carried out. Thereafter, polishing process is carried out again. Further, between polishing processes, dressing of the polishing cloth 5 by the diamond dresser and the water jet may be combined.

In the illustrated embodiment, the contact-type dresser of the first dressing unit 11 comprises the diamond dresser 10. However, the diamond dresser may be replaced with a brush dresser. Furthermore, pure water is used as the dressing liquid in the first dressing unit 11 and also as water jets in the second dressing unit 16. However, chemicals such as alkaline liquid or surface-active agent may be used in the first and second dressing units 11 and 16 for performing a chemical dressing action in addition to a mechanical dressing action.

Inasmuch as the polishing apparatus according to the

present invention is equipped with both the first dressing unit 11 having the contact-type dresser comprising the diamond dresser 10 and the second dressing unit 16 having the noncontact-type dresser comprising the water jet nozzles 15, 5 it is not necessary to replace two dressing units unlike the conventional polishing apparatus, and the two dressing units 11, 16 may be combined to carry out a desired pattern of dressing processes. If the polishing apparatus is applied to the fabrication of semiconductor devices, then semiconductor 10 devices can be manufactured in a high yield with high productivity.

Although a certain preferred embodiment of the present invention has been shown and described in detail, it should be understood that various changes and modifications may be made 15 therein without departing from the scope of the appended claims.

Industrial Applicability

The present invention relates to a polishing apparatus for polishing a workpiece such as a semiconductor wafer to a 20 planar finish, and is preferably utilized in manufacturing semiconductor devices.

CLAIMS

1. A polishing apparatus comprising:
a turntable with a polishing cloth attached thereto;
5 a top ring for holding and pressing a workpiece to be polished against said polishing cloth under a certain pressure;
a first dressing unit having a contact-type dresser for dressing said polishing cloth by bringing said contact-type dresser in contact with said polishing cloth; and
10 a second dressing unit having a noncontact-type dresser for dressing said polishing cloth with a fluid jet applied thereto.
2. A polishing apparatus according to claim 1, wherein
15 said contact-type dresser comprises one of a diamond dresser and an SiC dresser.
3. A polishing apparatus according to claim 1, wherein said fluid jet comprises a liquid jet having a pressure ranging
20 from 5 to 30 kg/cm².
4. A method of conditioning a polishing cloth attached to a turntable for polishing a workpiece, comprising:
dressing said polishing cloth with a first dressing unit
25 having a contact-type dresser as initial conditioning when said polishing cloth starts to be used; and
dressing said polishing cloth with a second dressing unit having a noncontact-type dresser between polishing processes, each for polishing said workpiece.
30
5. A method according to claim 4, wherein said contact-type dresser comprises one of a diamond dresser and an SiC dresser.

6. A method according to claim 4, wherein said noncontact-type dresser comprises a fluid jet nozzle for ejecting a fluid jet.

5

7. A method of conditioning a polishing cloth attached to a turntable for polishing a workpiece, comprising:

10 dressing said polishing cloth with a first dressing unit having a contact-type dresser as initial conditioning when said polishing cloth starts to be used; and

15 dressing said polishing cloth first with said first dressing unit and then with a second dressing unit having a noncontact-type dresser between polishing processes, each for polishing said workpiece.

8. A method according to claim 7, wherein said contact-type dresser comprises one of a diamond dresser and an SiC dresser.

20 9. A method according to claim 7, wherein said noncontact-type dresser comprises a fluid jet nozzle for ejecting a fluid jet.

1/4

FIG. 1





FIG. 2



2/4

FIG. 3A




FIG. 3B




FIG. 3C





FIG. 4



4/4

FIG. 5A





FIG. 5B



INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 99/01543

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 B24837/04 B24853/007		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 B248		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 754 525 A (EBARA CORPORATION) 22 January 1997 (1997-01-22) column 6, line 2 - line 21	1,2,4-9
Y	----	3
Y	US 5 421 768 A (FUJIWARA ET AL.) 6 June 1995 (1995-06-06) column 9, line 56 - line 57	3
A	EP 0 816 017 A (EBARA CORPORATION) 7 January 1998 (1998-01-07) abstract	2,5,8
A	US 5 716 264 A (KIMURA ET AL.) 10 February 1998 (1998-02-10) abstract	1,4,7

	--- --	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the international search 7 July 1999		Date of mailing of the international search report 14/07/1999
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Garella, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 99/01543

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 690 544 A (SAKURAI) 25 November 1997 (1997-11-25) abstract -----	1,4,7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 99/01543

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0754525	A	22-01-1997	JP 9029635 A	04-02-1997
			US 5857898 A	12-01-1999
US 5421768	A	06-06-1995	JP 2622069 B	18-06-1997
			JP 7009340 A	13-01-1995
EP 0816017	A	07-01-1998	JP 10071557 A	17-03-1998
US 5716264	A	10-02-1998	JP 9029619 A	04-02-1997
US 5690544	A	25-11-1997	JP 2647050 B	27-08-1997
			JP 8267354 A	15-10-1996